





TANKLESS WATER HEATERS MODEL CHART

specifications.

	Luxury Series			
				
Model	RL94i	RL94e	RL75i	RL75e
Dimensions (inches)	14w x 23h x 9d	14w x 23h x 9d	14w x 23h x 9d	14w x 23h x 9d
Weight (lbs / kg)	46.3 / 21.0	43.7 / 19.8	45.6 / 20.7	44.3 / 20.1
Installation Type	Indoor	Outdoor	Indoor	Outdoor
Min./Max. BTU (natural gas)	10,300/199,000	10,300/199,000	10,300/180,000	10,300/180,000
Min./Max. BTU (propane)	10,300/199,000	10,300/199,000	10,300/180,000	10,300/180,000
Energy Factor	0.82	0.82	0.82	0.82
Temp. Range (Residential)*	98°–140° F	98°–140° F	98°–140° F	98°–140° F
Temp. Range (Commercial)†	98°–185° F	98°–185° F	98°–160° F	98°–160° F
Min. Activation Rate	0.4 gpm	0.4 gpm	0.4 gpm	0.4 gpm
Flow Rate (70° / 50° Temp. Rise)	4.8 / 6.7	4.8 / 6.7	4.3 / 6.0	4.3 / 6.0
Hot Water Flow Rate Range	0.26–9.8 gpm	0.26–9.8 gpm	0.26–7.5 gpm	0.26–7.5 gpm
Controller (standard)§	MC-91-2US	MC-91-2US	MC-91-2US	MC-91-2US
Controllers (optional)§	MC-100-1, BC-100V-1, MCC-91-2 (for temperatures >140° F)			
Ultra Low NOx	no	yes	yes	yes
Warranty (Residential)	Limited 12-year on heat exchanger, 5-year on parts, 1-year on labor (5-year optional on labor)			
Warranty (Commercial)	Limited 5-year on heat exchanger, 5-year on parts, 1-year on labor (2-year optional on labor)			
Circ-Logic Compat. (S/N)**	DB.CA-016788	DC.BA-013335	N/A	N/A
Circ-Logic Compat. (P/N)***	N/A	N/A	REU-VC2528FFUD-US (A)	REU-VC2528WD-US (A)
Mobile Home Certified	yes	yes	yes	yes
Valves Shipped in Box	yes	yes	yes	yes
High Altitude Approved	Up to 10,200 ft.			
Certifications	AHRI, UPC, CSA, NSF, UMC, ENERGY STAR®			

* Can be selected by installer. Units come with a default maximum temperature of 120° F for increased safety and code compliance. An option to increase the maximum temp to 140° F is also available.

† To achieve temperatures over 140° F, an MCC-91 commercial controller must be purchased separately.

§ MC-91-2 controllers are backwards compatible with previous water heaters.

** Luxury Series Models (VC) – Circ-Logic™ availability beginning April 2012. VC models with serial numbers higher than those listed will ship with Circ-Logic installed. Lower serial numbers do not have Circ-Logic.

S/N = Serial Number
P/N = Part Number

*** Ultra Series Models (KB) – Circ-Logic availability beginning April 2012. KB models with serial numbers higher than those listed will ship with Circ-Logic installed. Lower serial numbers do not have Circ-Logic.